



**Housten series**

zone 1/2/21/22


These projectors with electrostatic powder coated aluminum injection housing and impact resistant tempered glass are used in places where the risk of burning-explosion is relatively low.

### Technical Details

Item	Power(W)	Description	Light Output (Lm)	Dimensions (mm)
EX-DFG1	100W	Ex-Housten Dau Gear 1	12800	422x330x80
EX-DFG2	150W	Ex-Housten Dau Gear 2	19200	422x330x80
EX-DFG3	200W	Ex-Housten Dau Gear 3	25600	422x330x80

### Technical Features

Warranty	: 5 Years
Lamp Type	: LED
Housing	: Aluminium
Optics	: Lens
Glass	: Tempered Glass
IP	: 66
Kelvin	: 3000-4000-5000-6500
CRI	: <80
Led Lifetime	: 50.000 h
Power Supply	: 110-240V 50-60Hz
Op. Temp.	: -20°C / +45°C



Quality Certificate

**Ex II 2G Ex EB IIB T4 Gb**

**Ex II 2D Ex TB IIIB T135°C Db, IP66**

**EX Certificate No : IEP 25 ATEX 1626X**

**CE TSE RoHS ISO**

Scan to View  
Catalog



Edea Elektrik Aydınlatma Dış Ticaret Ltd. Şti.

Head Office & Factory

İkitelli OSB Mah. Dersan A Blok Sk. Trios 2023, A Blok No:1, İç Kapı No:47

34490 Başakşehir / İstanbul / Türkiye

Phone: +90 212 812 03 27 E-mail: info@edealight.com

Copyright © 2026 by Edea Elektrik Aydınlatma Dış Ticaret Ltd. Şti.