

Product Datasheet

PAVO SQUARE



Linear Pendant Luminaire



Description:

Suitable for suspended or surface mounting on ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

Technical Features:

| | | | |
|---------------------|-----------------------|---------------------|--------------------|
| Installation | : Surface / Suspended | Kelvin | : 3000-4000-6000 |
| Warranty | : 5 years | CRI | : >90 |
| Lamp Type | : LED | LED Lifetime | : 80.000 h |
| Housing | : Aluminium | Power Supply | : 110-240V 50-60Hz |
| Glass | : Difusser | Op. Temp. | : -20°C / +45 °C |
| IP | : 20 | | |

Prometrical Data:



Technical Details:

| Item | Power (W) | Description | Light Output (Lm) | Dimensions (mm) |
|-------|-----------|--------------------|-------------------|-----------------|
| PLGG1 | 41 | Pavo Square Gear 1 | 4650 | 300-600-80 |
| PLGG2 | 55 | Pavo Square Gear 1 | 6200 | 600-600-80 |
| PLGG3 | 70 | Pavo Square Gear 1 | 7800 | 300-1200-80 |

Technical Options:

- *Dali
- *Dimmer
- *Emergency Kits

Colours



Quality Certificiate:

