

# POLEN

## Wall Luminaire




### Description:



Corrosion resistant die cast aluminium alloy. Thermal shock resistant safety glass. Weatherproof and durable silicone rubber gasket. Ultraviolet stabilized polyester powder coat finish in black, dark, gray and light gray finish. Convenient to be used with COB led option. Designed for single-side light output. Luminaire can be installed in any burning position.

### Technical Features:

<b>Installation</b>	: Surface	<b>Kelvin</b>	: 3000K-4000K-5000K-6500K
<b>Warranty</b>	: 5 years	<b>CRI</b>	: >80
<b>Lamp Type</b>	: COB	<b>LED Lifetime</b>	: 25.000 h
<b>Housing</b>	: Aluminium	<b>Power Supply</b>	: 110-240V 50-60Hz
<b>Glass</b>	: Difusser	<b>Op. Temp.</b>	: -20°C / +45 °C
<b>IP</b>	: 44		



### Prometrical Data:



### Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
PWG1	6	Polen Wall Luminaire Gear 1	330	300-173
PWG2	12	Polen Wall Luminaire Gear 2	660	300-173
PWG3	18	Polen Wall Luminaire Gear 3	990	300-173
PWG4	24	Polen Wall Luminaire Gear 4	1320	300-173

### Technical Options:

- \*Dali
- \*Dimmer
- \*Emergency Kits

### Colour



### Quality Certificate:



Tel : +90 212 812 03 27

:

Web : [www.edealight.com](http://www.edealight.com)

EDEA LIGHT reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.