

RUTEN

Wall Luminaire





Description:

Corrosion resistant die cast aluminium alloy. Thermal shock resistant safety glass. Weatherproof and durable silicone rubber gasket. Ultraviolet stabilized polyester powder coat finish in black, dark, gray and light gray finish. Convenient to be used with COB led option. Designed for single-side light output. Luminaire can be installed in any burning position.

Technical Features:

Installation	: Surface	Kelvin	: 3000K-4000K-5000K-6500K
Warranty	: 5 years	CRI	: >80
Lamp Type	: LED	LED Lifetime	: 25.000 h
Housing	: Aluminium	Power Supply	: 110-240V 50-60Hz
Glass	: Difusser	Op. Temp.	: -20°C / +45 °C
IP	: 44		

Prometrical Data:



Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
RWG1	6	Ruten Wall Luminaire Gear 1	330	300-300-173
RWG2	12	Ruten Wall Luminaire Gear 2	660	300-300-173
RWG3	18	Ruten Wall Luminaire Gear 3	990	300-300-173
RWG4	24	Ruten Wall Luminaire Gear 4	1320	300-300-173

Technical Options:

- *Dali
- *Dimmer
- *Emergency Kits

Colour

Black



Quality Certificate:



Tel : +90 212 812 03 27

:

Web : www.edealight.com

EDEA LIGHT reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.