

## TATA SURFACE

### Downlight Luminaire





**Description:**

Suitable for surface mounting on ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

**Technical Features:**

<b>Installation</b>	: Surface	<b>Kelvin</b>	: 3000-4000-6000
<b>Warranty</b>	: 3 years	<b>CRI</b>	: >90
<b>Lamp Type</b>	: LED	<b>LED Lifetime</b>	: 80.000 h
<b>Housing</b>	: Aluminium	<b>Power Supply</b>	: 110-240V 50-60Hz
<b>Glass</b>	: Difusser	<b>Op. Temp.</b>	: -20°C / +45 °C
<b>IP</b>	: 20		

**Prometrical Data:**



**Technical Details:**

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
TDG1	7	Tata 2" Downlight Gear 1	700	Q100-150
TDG2	10	Tata 3" Downlight Gear 2	875	Q100-150
TDG3	16	Tata 4" Downlight Gear 3	1486	Q126-150
TDG4	18	Tata 5" Downlight Gear 4	1897	Q150-150
TDG5	20	Tata 6" Downlight Gear 5	2107	Q150-150

**Technical Options:**

- \*Dali
- \*Dimmer
- \*Emergency Kits

**Colours**



**Quality Certificate:**



Tel : +90 212 812 03 27

:

Web : [www.edealight.com](http://www.edealight.com)

EDEA LIGHT reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.