

TWIST



Directional Downlight Luminaire



Description:

Suitable for recessed mounting in unventilated or ventilated ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

Technical Features:

Installation	: Recessed	Kelvin	: 3000-4000-6000
Warranty	: 5 years	CRI	: >80
Lamp Type	: LED	LED Lifetime	: 50.000 h
Housing	: Aluminium	Power Supply	: 110-240V 50-60Hz
Glass	: Reflector	Op. Temp.	: -20°C / +45 °C
IP	: 20		

Prometrical Data:



Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
TAG1	1x25	Twist Directional Gear 1	3125	150-150-100
TAG2	2x25	Twist Directional Gear 2	6250	285-150-100
TAG3	3x25	Twist Directional Gear 3	9375	415-150-100

Technical Options:

- *Dali
- *Dimmer
- *Emergency Kits

Colours



Quality Certificate:



Tel : +90 212 812 03 27

:

Web : www.edealight.com

EDEA LIGHT reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.